


SECTION

LEGEND:

- (A) TECHO-BLOC CAP UNIT SECURED TO UNIT BELOW WITH CONCRETE ADHESIVE
- (B) SEMMA DOUBLE-SIDED WALL UNIT
- (C) CONNECTOR
- (D) EMBEDMENT DEPTH, 6" (150 MM) MIN.
- (E) TOTAL HEIGHT (VARIABLE)
- (F) TOPSOIL
- (G) LOW PERMEABILITY SOIL
- (H) FREE DRAINING AGGREGATE, 12" (300 MM) THICK MIN.
- (I) GEOTEXTILE
- (J) PERFORATED DRAIN, 4" (100 MM) DIA. MIN.
- (K) COMPACTED GRANULAR LEVELING PAD, 6" (150 MM) THICK MIN. THICKNESS ACCORDING TO PROJECT SPECIFIC CONDITIONS

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5058-021.



RETAINING WALLS

RETAINING WALLS (GRAVITY): SEMMA